



## GS-IP-705BC

Weatherproof IR Bullet  
3.6mm Fixed Megapixel Lens  
2.3MP Exmor Color IP Camera

The GSI Plug and Play IP camera series has Ultra High 1920 x 1080 pixels of color resolution using Sony's Exmor Sensor. Using the 2.3MP CMOS chip, this gives this camera realistic colors and high sensitivity to low light conditions. Has high power IR LED array for Day/Night applications. This IP camera has 7 X the resolution of a traditional analog camera. With its versatile 3-Axis mount it can be installed on the ceiling or directly on the wall. Built in PoE allows easy installation with data and power on a single Cat5E/Cat6 line. It is seamless plug and play with GSI POE NVRs.



### Features:

- 1/2.8" SONY Exmor Megapixel CMOS Sensor
- Plug and Play with GSI POE NVRs
- 2.3 Megapixel 1920 x 1080 Resolution at 30FPS
- Versatile 3-Axis Camera Mount
- 3.6 mm Megapixel Fixed Lens
- High Power IR LED Array (Up to 50ft Illumination)
- Aesthetically Pleasing Housing for Indoor/Outdoor Use
- Onvif and PSIA Conformant
- IP 66 Weather Rating
- Weatherproof Bullet
- True Day/Night ICR
- H264 Compression
- PoE or 12VDC Input
- Web interface and Mobile App Support
- Solid and compact Aluminum construction

### Specifications:

Signal System	NTSC IP
Image Sensor	1/2.8" 2.3MP SONY Exmor CMOS Sensor
DSP	Sony IMX238 + FH8520
Series	Gold
Pixel Count	1920(H) x 1080(V)
Scanning System	2:1 Interlace
Scanning Frequency (V)	59.94Hz
Resolution	2.3 Megapixel
Min. Illumination	0.2 LUX (IR OFF) 0 LUX (IR On)
Light Compensation	Super BLC
S/N Ratio	More than 52dB (AGC OFF)
Shutter Speed	1/60 ~ 1/1000,000 sec.
Video Output	RJ45 10/100
Sync System	Internal
Voltage	12VDC or POE Support
Power Consumption	450mA (Max IR ON)
Dimensions	3.5" x 8.1"
Weight	1.2 lbs
Operating Temperature	-10°C to 50°C



### WARNING:

**Do Not Point Camera Directly into the sun.**

**Do Not cut video or power wires**

**Observe Correct Voltage and Polarity**

**Failure to Observe Warnings May Void Warranty**

