


# SELECT ALERT



GS-SA5000-R



## PRODUCT OVERVIEW

Here is a highly effective way to alert you to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries. The combination of alarm and super bright flashing LEDs offers excellent protection for an array of circumstances as they draw attention in a hurry. Select-Alert allows you to choose its function and can be used as a cabinet alarm, door/exit alarm, flashing light linked with a push button/switch, tornado siren, burglar alarm or an alert for many types of emergency situations.

## HOW IT WORKS

When installed as a cabinet or door alarm, with the optional reed switch and magnet, Select-Alert emits an ear piercing siren and the LEDs flash when the protected unit is opened. The alarm and strobe have independent timing choices of: 15 seconds, 30 seconds, 60 seconds or continuous and the alarm has an option of 32 tones. Can be powered by a 9 VDC battery or external 12 - 24 volts. Flush or surface mount Select-Alert is available in amber, green, blue, red or white.

## KEY FEATURES

### General Information

- Alerts to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries.
- Alarm offers 32 tones.
- Includes ten high intensity LEDs.
- For indoor use only.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

### Construction

- Durable, polycarbonate construction.

### Installation

- Includes a tamper switch which prevents it from being removed from a wall.
- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).

### Electronics

- May be set for a piercing 100 dB alarm or a softer 85 dB.
- One Form "C" dry relay contact output.
- Powered by a 9 VDC battery (not included) or external 12 – 24 volts.
- Low battery indicator.

### Options

- Can be used as a cabinet alarm, door alarm, link with push button/switch or as a burglar alarm.
- Available with amber, green, blue, red or white lens.

# Select Alert

## Dimensions and Technical Information

### MODELS AVAILABLE


GS-SA5000-A	Amber
GS-SA5000-B	Blue
GS-SA5000-G	Green
GS-SA5000-R	Red
GS-SA5000-W	White

### WARRANTY


Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

### SPECIFICATIONS

<b>Operating voltage</b>	Internal 9 VDC battery (not included) Remote power 12-24 VDC
<b>Power consumption</b>	Stand by: 50 $\mu$ A Siren low volume: 85mA Siren high volume: 90mA Strobe: 25mA
<b>Siren Volume</b>	Low: 85 dB at 1' High: 100 dB at 1'
<b>Alarm and Strobe Timing</b>	Independent control for siren and strobe: 15s, 30s, 60s, continuous
<b>Low Battery Warning</b>	LEDs flash once every 30 seconds
<b>Form C dry contacts</b>	0-30VAC/DC, 1 Amp Contacts reset after longest alarm setting
<b>Key Switch</b>	Alarm on: normally closed
<b>Alarm Circuit</b>	Open circuit (close goes to alarm)
<b>Alarm Tone</b>	32 selectable sounds



FRONT



SIDE